








# Dielectri



<b>HS CODE</b>
63079098
<b>CARTON SIZE / PCS.</b>
80 x 40 x 24 cm / 10
<b>AET N°2777/10962-03/E01-01</b>
<b>Satra Technology Europe Ltd., N° 2777,</b> Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland
<b>MODULE D FI14/14003.01</b>
<b>SGS Fimko Oy, N°0598</b> Takomotie 8, 00380 HELSINKI, Finland
<b>AET (UKCA) N°AB0321/16021-01/E01-01</b>
<b>Satra Technology Centre, N°0321</b> Wyndham Way, Telford Way, Kettering Northamptonshire, NN16 8SD, United Kingdom
<b>MODULE D 11 IN14/14003</b>
<b>SGS United Kingdom Ltd., N°0120</b> Unit 202B, Worle Parkway, Weston-super-Mare, BS22 6WA, United Kingdom

REF.	FA 30 405 15
LG.  KG	1.5 m (connectors included)
CE	EN 355:2002
MAT.	 30 mm PES
	45 mm
	P & 
	NO
+	MAX. DIELECTRIC RESISTANCE = 14 kV + PPE-R 11.063
	2.03 KG



**Largeur de l'absorbeur d'énergie**  
Width of the energy absorber  
**Ancho del absorbedor de energía**  
Larghezza del assorbitore di energia  
**Breite des Falldämpfers**

LG.



**Longueur Poids maxi utilisateur**  
**Length** Max. user weight  
**Longitud** Peso máximo del usuario  
**Lunghezza** Peso Max. dell'utente  
**Länge** Höchstgewicht des Benutzers



**Matière connecteur haut / connecteur bas**  
Material of top connector / bottom connector  
**Material conector alto / conector bajo**  
Materiale connettore alto / connettore basso  
**Material oberes / unteres Verbindungselement**

+

**Point fort**  
Key feature  
**Ventaja principal**  
Punti forti  
**Produktvorteil**



**Homologué pour le travail à proximité d'arêtes vives**  
Approved for work near sharp edges  
**Homologado para trabajo cerca de aristas vivas**  
Omologato per lavoro in prossimità di spigoli vivi  
**Zugelassen für Arbeiten in der Nähe scharfer Kanten**