



Neshoba™ ANSI • CE • CSA •

Frameless design with thin flexible temples // Ultra lightweight spectacle
– 16 gm

Black Temples | 7 Variations

	S9710S ●●●	Clear
	S9710ST ●●●	Clear H2X AF
	S9720S ●●●	Gray
	S9720ST ●●●	Gray H2X AF
	S9730S ●●●	Amber
	S9780S ●●●	I/O Mirror
	S9780ST ●●●	I/O Mirror AF



General Specifications

Weight: 16 gm
 PD: 64 mm
 Bridge: 12.3 mm
 Lens base: 9.5 curve
 Lens size diagonal: 75.8 mm
 Lens size vertical: 43.3 mm
 Lens thickness: 1.6 mm
 Overall length [lens - tip]: 151 mm
 Overall width [hinge - hinge]: 135 mm
 Closest point between lens: 14.5 mm

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 S: Special Purpose
UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV
Visible Light Filters
 L1.7: 55% max. visible light
 L2.5: 29% max visible light

Part No.

S9710S
 S9710ST
 S9720S
 S9720ST
 S9730S
 S9780S
 S9780ST

Lens Marking

P Z87 + U6
 P Z87 + U6
 P Z87 + U6 L2.5
 P Z87 + U6 L2.5
 P Z87 + U6
 P Z87 + U6 L1.7
 P Z87 + U6 L1.7

Temple Marking

P Z87 + / P c SEI CAN/CSA Z94.3-15
 P Z87 + / P c SEI CAN/CSA Z94.3-15
 P Z87 + / P c SEI CAN/CSA Z94.3-15
 P Z87 + / P c SEI CAN/CSA Z94.3-15
 P Z87 + / P c SEI CAN/CSA Z94.3-15
 P Z87 + / P c SEI CAN/CSA Z94.3-15

Materials

Lens: polycarbonate
 Temples: polycarbonate
 Hinge: polycarbonate
 Screw: stainless steel

Temple Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact