






Ø 13 mm



HS CODE
83081000
CARTON SIZE / PCS.
40 x 30 x 20 cm / 25
Certificate of Test based on Technical reports n°SPC0211748/1306/6 Ext. 1, SPC0309308/2108 Issue 2 Ext. 1
Satra Technology Centre, N°0321 Wyndham Way, Telford Way, Kettering Northamptonshire, NN16 8SD, United Kingdom


REF.	FA 60 009 00
CE	EN 795:2012 Type A
	x3 (TS 16415 :2013)
MAT.	
R (kN) / MBS (kN)	12 kN / 23 kN
	M12 Ø 13 mm (CONCRETE, METAL)
	0.33 KG



Nombre d'utilisateurs
Number of users
Cantidad de usuarios
Cantidad di utilizzatori
Anzahl der Benutzer

R (kN) / MBS (kN)

Résistance statique (en kN) / Résistance à la rupture
Static strength / Minimum Breaking Strength
Resistencia estática (en kN) / Resistencia a la ruptura (en kN)
Resistenza statica (in kN) / Resistenza alla rottura (in kN)
Statische Festigkeit (in kN) / Bruchfestigkeit (in kN)



Fixations à utiliser / Dimensions de la structure d'accueil
Fasteners to use / Dimensions of the receiving structure
Fijaciones que deben usarse / Dimensiones de la estructura receptora
Elementi di fissaggio da utilizzare / Dimensioni della struttura ospitante
Zu verwendende Befestigungen / Abmessungen der Aufnahmestruktur