

Melixon-S
EXO

FA 20 402 07EXO = FA 20 402 07 + FA 20 EXO 07
FA 20 402 10EXO = FA 20 402 10 + FA 20 EXO 10
FA 20 402 15EXO = FA 20 402 15 + FA 20 EXO 15



HS CODE
84798997
CARTON SIZE / PCS.
FA 20 402 07EXO : 48 x 28 x 32 cm / 1 FA 20 402 10EXO : 40 x 30 x 24 cm / 1 FA 20 405 15EXO : 62 x 34 x 37 cm / 1
AET (UE) N°2777/10829-03/E08-01 (FA 20 402 07, FA 20 402 10)
AET (UE) N° 2777/10833-02/E01-02 (FA 20 402 15)
Satra Technology Europe Ltd., N° 2777, Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland
MODULE D FI14/14003.01
SGS Fimko Oy, N°0598 Takomotie 8, 00380 HELSINKI, Finland

REF.	FA 20 402 07EXO	FA 20 402 10EXO	FA 20 402 15EXO
 LG. KG	7 m	10 m	15 m
	EN 360:2002		
 MAT.	Polyamide 6 - 30% fiber glass		
 STEEL	STEEL Ø4.8 mm		
 QUARTER / DOUBLE ACTION	STEEL		
 360°	x2		
 R(kN)	12 kN		
 YES	YES		
+	Integrated exoskeleton FA 20 EXO 07	Integrated exoskeleton FA 20 EXO 10	Integrated exoskeleton FA 20 EXO 15
 Kg	4.58 KG	5.35 KG	8.74 KG




Longueur Poids maxi utilisateur
Length Max. user weight
Longitud Peso máximo del usuario
Lunghezza Peso Max. dell'utente
Länge Höchstgewicht des Benutzers

MAT.



Matière carter / câble
 Material of casing / wire rope
Material cárter / cable
 Material dei carter / cavo
Material Gehäuse / Seil



Matière connecteur haut / connecteur bas
 Material of top connector / bottom connector
Material conector alto / conector bajo
 Materiale connettore alto / connettore basso
Material oberes / unteres Verbindungselement



Nombre d'émerillons
 Number of swivels
Cantidad de eslabones giratorios
 Numero di tornichetti
Anzahl der Wirbel



Homologué pour le travail à proximité d'arêtes vives
 Approved for work near sharp edges
Homologado para trabajo cerca de aristas vivas
 Omologato per lavoro in prossimità di spigoli vivi
Zugelassen für Arbeiten in der Nähe scharfer Kanten